

BUILT-IN ROLLER SHUTTERS



PRODUCT INNOVATION

- Patented lath design to provide small roll zones as standard
- Minimal box and lintel protrusion into building
- Consistency of profile across multiple widths

TYPICAL APPLICATIONS

- Commercial & community buildings
- Residential
- Garages

FEATURES

- High strength extruded aluminium profiles
- Fully insulated cavity closer profiles
- Shutter curtain retained within side guides

OPTIONS

- Polyester powder coat
- Solid or perforated profiles
- Structural steel or non-structural PVC box
- Frame former
- Range of controls and safety

BUILT-IN ROLLER SHUTTERS

APPROVED DIMENSIONS

Minimum width: 1000mm

Maximum width: 6000mm

Minimum height: 1000mm

Maximum height: 5000mm

SHUTTER CURTAIN

Extruded aluminium profiles

Polyester powder coated in standard RAL/BS colour

Option to perforate

Varying size slats to allow intelligent, small roll zones



BOTTOM RAIL & FRAMES

Extruded aluminium bottom rail

Extruded aluminum guide profiles recessed into cavity of external wall complete with fully insulated cavity closer



OPERATION

240v Tube Motor with option for manual override

Sprung with bottom rail key lock

CONTROLS

Range of compatible controls including push button, key switch, or remote control

Safety on close as assessment directs

LINTEL/HEADBOX

Structural

Fully structural lintel system built into building construction to support imposed loads. Lintels are dependent on structural loads and shutter size

Non-Structural

PVC non load-bearing box to be incorporated in wall make up. Box size dependent on size of shutter

Distributor