

700 SERIES DATA SHEET



BOLT ON ROLLER SHUTTERS



FEATURES

- Compact roll zones
- High strength and low weight
- Twin skin extruded aluminium lath
- Polyester powder coated to any standard RAL /BS colour

OPTIONS

- Range of switches and access control
- Can be partially or fully perforated and punched

ALL-ALUMINIUM CONSTRUCTION

- Twin part roll formed aluminium casing
- Slimline extruded aluminium guides
- Smooth and quiet operation with roller guide entry

TYPICAL APPLICATIONS

Suitable new build applications include:

- Medium risk commercial buildings
- Public facilities - schools, universities, community centers
- Retail outlets - point of sale gantries
- Cultural Buildings
- Residential

700 SERIES DATA SHEET



BOLT ON ROLLER SHUTTERS

PRODUCT REFERENCE

Xonar 700 Roller Shutter

APPROVED DIMENSIONS

Maximum width: 3200mm	Maximum height: 4000mm
Minimum width: 1000mm	Minimum height: 1000mm

SHUTTER CURTAIN

40mm twin wall

Extruded aluminium profiles

Finish as delivered: polyester powder coated in standard RAL/BS colour

Option to fully or partially perforate or punched

OPERATION

Motorised to allow controlled ascent and descent

Tube Motor - Low duty cycle, or where limited to single phase supply

External Drive Motor - High duty cycle or for larger apertures

FRAMES/GUIDES

Slimline extruded aluminium guides mounted directly to structure

Finish as delivered: polyester powder coated in standard RAL/BS colour



SUBSTRATE

Installation onto:

Brickwork
Blockwork
Steelwork
Timber

BOTTOM RAIL

Extruded aluminium section with rubber sealing gasket

Finish as delivered: polyester powder coated in standard RAL/BS colour

CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or possible to integrate into building management systems and third party alarms

Safety on close as assessment directs

Battery backup options

Distributor

