

630 SERIES DATA SHEET



BUILT IN ROLLER SHUTTERS FOR LARGER OPENINGS



FEATURES

- Structural steel lintel or non-structural UPVC box
- Large spans possible
- Polyester powder coated to any standard RAL /BS colour
- Twin wall extruded aluminium lath

OPTIONS

- Frame formers for combined cavity closer and guide
- Range of switches and access control
- Can be partially or fully perforated or punched

INSTALL

- Powder coated extruded aluminium guide with large return flanges
- Fully insulated cavity closer
- Ply temporary access panel to rear of lintel

TYPICAL APPLICATIONS

Suitable applications include:

- Medium risk commercial buildings
- Public facilities - schools, universities, community centers
- Cultural Buildings
- Residential
- Garage Doors

630 SERIES DATA SHEET



BUILT IN ROLLER SHUTTERS FOR LARGER OPENINGS

PRODUCT REFERENCE

Xonar 630 Roller Shutter

APPROVED DIMENSIONS

Maximum width: 6000mm Maximum height: 6000mm

Minimum width: 1000mm Minimum height: 1200mm

SHUTTER CURTAIN

60mm twin wall

Extruded aluminium profiles

Finish as delivered: polyester powder coated in standard RAL/BS colour

FRAMES/GUIDES

Extruded aluminium guide profiles recessed into cavity of external wall complete with fully insulated cavity closer

Finish as delivered: polyester powder coated in standard RAL/BS colour

LINTEL/HEADBOX

Structural

Fully structural lintel system built into building construction and support imposed loads. Lintels are dependent on structural loads and shutter size

Non-Structural

PVC non load-bearing box to be incorporated in wall make up. Box size dependent on size of shutter

OPERATION

240v Tube Motor to allow controlled ascent and descent



SUBSTRATE

Installation onto:

Brickwork

Blockwork

SFS & Timber Frame

BOTTOM RAIL

Extruded aluminium section with rubber sealing gasket

Finish as delivered: polyester powder coated in standard RAL/BS colour

CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or possible to integrate into building management systems and third party alarms

Safety on close as assessment directs

Battery backup options

Distributor