



## STACK TECHNOLOGY

- Reduced headroom for applications with limited space
- Inline or double stack
- More than 80% free airflow
- Large maximum width
- Self-locking to prevent lifting
- No locks and cannot be manually forced open



## TYPICAL APPLICATIONS

- Residential folding doors
- Car Park entrances
- Retail outlets



## OPTIONS

- Stainless Steel or Polyester powder coated to any standard Ral/BS colour
- High or low duty cycle electrical motors
- Curved and Corner solutions possible with no intermediate guide rails

# COMPACT

PRODUCT DATASHEET



# STACKDOOR

## APPROVED DIMENSIONS

Minimum width: 1000mm      Maximum width: 20000mm

Minimum height: 500mm      Maximum height: 7000mm

## SHUTTER CURTAIN

Solid Steel pins secured into horizontal steel profiles



## BOTTOM RAIL & FRAMES

Reinforced extruded aluminum bottom rail section

Heavy duty extruded aluminium guide rails anchored direct to the structure

No intermediate guides necessary



## OPERATION

Motorised to allow controlled ascent and descent

Tube Motor - Low duty cycle, or where limited to single phase supply

External Drive Motor - High duty cycle for larger apertures



## CONTROLS

Range of compatible controls including rotary switch, key switch, remote [control] and emergency manual crank

Safety on close as assessment directs

Distributor