

# IR2 DATA SHEET

# INTIMIDATOR

HIGH PERFORMANCE INDUSTRIAL DOORS

A1 (SR1)

**B3 (SR2)**

C5 (SR3)

D10 (SR4)

LPS 1175 CERTIFIED INDUSTRIAL DOORS



## ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 8, B3 (SR2)
- Secured by Design Police Preferred Specification



## TYPICAL APPLICATIONS

- Medium risk commercial buildings
- Utilities Buildings
- Data centres



## OPTIONS

- Aluminium, galvanised steel or stainless steel shutter curtain construction
- Single skin steel curtain construction with full or partial perforation
- Polyester powder coated to any standard RAL/BS colour
- Manual or auto locking
- High or standard duty cycle motors
- Thermal insulation upgrade
- Acoustic insulation upgrade

# IR2 DATA SHEET

# INTIMIDATOR

HIGH PERFORMANCE INDUSTRIAL DOORS

A1 (SR1)

**B3 (SR2)**

C5 (SR3)

D10 (SR4)

LPS 1175 CERTIFIED INDUSTRIAL DOORS

## PRODUCT REFERENCE

- Intimidator IR2 Industrial Door

## APPROVED DIMENSIONS

- Maximum width: 8000mm
- Maximum height: 8000mm
- Minimum width 1000mm
- Minimum height: 1000mm



## SHUTTER CURTAIN

- Single Wall Aluminium
- Single Wall Galvanised Steel
- Single Wall Perforated Steel
- Double Wall Aluminium
- Double Wall Galvanised Steel
- Double Wall Stainless Steel

## FRAMES/GUIDES

- Two-part galvanised steel guide with rubber seals



## SUBSTRATE

- Brickwork
- Blockwork
- Concrete
- Structural Steelwork
- Sub assembly steel framework

## OPERATION

- Hold-to-run operation with manual locks
- Automatic operation with electronic locks
- Safety on close as assessment directs

## BOTTOM RAIL

- Extruded aluminium
- Reinforced steel
- Weather seal

Distributor