

NBS Type Specification

- **Description:** Industrial Door System with Independent Certification
- **Product reference:** Intimidator IR1 Industrial Door
- **Manufacturer:** CGT Security
 - 1 Darwin Close, Reading, Berkshire, RG2 0TB
 - Tel: 0330 024 9409
 - Email: sales@cgtsecurity.com
- **Company Certification:** ISO 9001
- **Product Certifications:** BS EN 13241-1, BS EN 12604, BS EN 12453
- **Product Performance:** Product certified to LPS 1175 Issue 8, A1 (SR1), Secured By Design Official Police Preferred Specification.
- **Arrangement:** Top rolling industrial door with metal slats.
- **Thermal performance:** [Option - Thermal insulation upgrades available. Contact manufacturer to obtain more details.](#)
- **Acoustic performance:** [Option - Acoustic insulation upgrades available. Contact manufacturer to obtain more details.](#)
- **Opening Sizes:**
 - [Certified width - Maximum 8000mm](#)
 - [Certified height – Maximum 8000mm](#)
- **Shutter Curtain:**
 - **Material:** Standard – Single wall galvanised steel. [Options available - Single wall aluminium, single wall perforated steel, double wall aluminium, double wall galvanised steel, or double wall stainless steel.](#)
 - **Finish:** Standard – Galvanised finish for steel, mill finish for aluminium or stainless steel. [Options -Polyester powder coated to 25 microns available. Standard RAL/BS code. Marine grade powder coat. Anodising on aluminium version.](#)
- **Frame/Guides:**
 - **Material:** Two-part heavy duty galvanised wind lock steel guides complete with rubber seals. Internally reinforced and supplied with heavy duty fixings in accordance with LPS 1175 requirements.
 - **Finish:** Galvanised steel.
- **Bottom Rail:**
 - **Material:** Internally reinforced extruded aluminium with weather seal.
 - **Finish:** Standard – Mill finish. [Polyester powder coated to 25 microns. RAL/BS code.](#)
- **Hood:** [Option – 3-sided folded galvanised steel hood. Option to powder coat to RAL/BS code.](#)

NBS Type Specification

- **Motor:** External Direct Drive Motor. Standard duty cycle. [Option – high duty cycle](#)
- **Suitable Substrate:** To be mechanically anchored directly to brickwork, blockwork, concrete, structural steelwork, or sub assembly steel framework as certified to LPS 1175 issue 8, security rating A1 (SR1).
- **Operation:** Standard - Hold-to run operation with manual locks. Safety on close as assessment directs. [Option - automatic operation with electronic locks.](#)
- **Installation & Fixing:** In accordance with CGT Security Installation guidelines and recommendations.



LPS 1175 Issue 8
Cert. No. 1396d



Assessed to ISO 9001
Cert/LPCB ref.1396

Secured by Design



Police Preferred Specification

All products are based on standard specifications unless otherwise indicated. [Options available in blue text.](#)

The large range of options available means bespoke requirements can be accommodated. Please contact the manufacturer to discuss further if the exact product requirement is not covered by this specification.