



NBS Type Specification

- Description: Bolt-On Roller Shutter System
- Product reference: Vortex Bolt-On Roller Shutter
- Manufacturer: CGT Security
 - 1 Darwin Close, Reading, Berkshire, RG2 0TB
 - Tel: 0330 024 9409
 - Email: sales@cgtsecurity.com
- Company Certification: ISO 9001
- Product Certifications: BS EN 13241-1, BS EN 12604, BS EN 12453
- Product Performance: Certified to BS EN 13241-1 wind load resistance up to Class 5.
- **Arrangement** Top rolling shutter with minimal size shutter box mounted at high level. Roll size up to 50% smaller than a standard roller shutter.
- Opening Sizes:
 - Maximum certified width 6000mm
 - o Minimum certified width 1000mm
 - o Maximum certified height 5000mm
 - o Minimum certified height 1000mm
- Shutter Curtain:
 - Material: Extruded aluminium lath profile to grade 6063 T6. Patented lath design. Varying size slats to provide intelligent, small roll zones. Fully retained shutter curtain.
 - o Option Perforated profiles.
 - o **Finish:** Polyester powder coated to 25 microns.
 - o Colour: Standard RAL/BS code.
- Frame/Guides:
 - o Material: Extruded aluminium guide profiles with snap cover.
 - o **Finish:** Polyester powder coated to 25 microns.
 - Colour: Standard RAL/BS code
- Bottom Rail:
 - Material: Extruded aluminium.
 - o **Finish:** Polyester powder coated to 25 microns.
 - Colour: Standard RAL/BS code.
- Motor:
- o 240v Tube Motor.
- Option manual override.







NBS Type Specification

- Hood:
 - o Material: Minimal size, two part aluminium head box
 - o **Finish:** Polyester powder coated to 25 microns.
 - o Colour: Standard RAL/BS code.
- Operation/Controls: Safety on close as assessment directs. Options Safety edge for safety on close. Full range of compatible control options available including push button, key switch, or remote control.
- **Installation & Fixing:** In accordance with CGT Security Installation guidelines and recommendations.

All products are based on standard specifications unless otherwise indicated. Options available in blue text.

The large range of options available means be spoke requirements can be accommodated. Please contact the manufacturer to discuss further if the exact product requirement is not covered by this specification.

