

IR1 DATA SHEET

INTIMIDATOR®

HIGH PERFORMANCE INDUSTRIAL DOORS

A1 (SR1)

B3 (SR2)

C5 (SR3)

D10 (SR4)

LPS 1175 CERTIFIED INDUSTRIAL DOORS



ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 8, A1 (SR1)
- Secured by Design Police Preferred Specification

TYPICAL APPLICATIONS

- Lower risk commercial buildings
- Warehouses
- Production Facilities

OPTIONS

- Aluminium, galvanised steel or stainless steel shutter curtain construction
- Single skin steel curtain construction with full or partial perforation
- Polyester powder coated to any standard RAL/BS colour
- Manual or auto locking
- High or standard duty cycle motors
- Thermal insulation upgrade
- Acoustic insulation upgrade

IR1 DATA SHEET

INTIMIDATOR®

HIGH PERFORMANCE INDUSTRIAL DOORS

A1 (SR1)

B3 (SR2)

C5 (SR3)

D10 (SR4)

LPS 1175 CERTIFIED INDUSTRIAL DOORS

PRODUCT REFERENCE

- Intimidator IR1 Industrial Door

APPROVED DIMENSIONS

- Maximum width: 8000mm
- Maximum height: 8000mm
- Minimum width: 1000mm
- Minimum height: 1000mm



SHUTTER CURTAIN

- Single Wall Aluminium
- Single Wall Galvanised Steel
- Single Wall Perforated Steel
- Double Wall Aluminium
- Double Wall Galvanised Steel
- Double Wall Stainless Steel

FRAMES/GUIDES

- Two-part galvanised steel guide with rubber seals



SUBSTRATE

- Brickwork
- Blockwork
- Concrete
- Structural Steelwork
- Sub-assembly steel framework

OPERATION

- Hold-to-run operation with manual locks
- Automatic operation with electronic locks
- Safety on close as assessment directs

BOTTOM RAIL

- Extruded aluminium
- Weather seal

Distributor