

# IR4 DATA SHEET

# INTIMIDATOR®

HIGH PERFORMANCE INDUSTRIAL DOORS

A1 (SR1)

B3 (SR2)

C5 (SR3)

**D10 (SR4)**

LPS 1175 CERTIFIED INDUSTRIAL DOORS



## ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 8, D10 (SR4)
- Secured by Design Police Preferred Specification



## TYPICAL APPLICATIONS

- High risk commercial buildings
- Government & Defence
- Critical Infrastructure
- Laboratories



## OPTIONS

- Galvanised steel or stainless steel curtain construction
- Polyester powder coat to any standard RAL / BS colour
- Manual or auto locking
- High or standard duty cycle motors
- Thermal insulation upgrade
- Acoustic insulation upgrade



# IR4 DATA SHEET

# INTIMIDATOR®

HIGH PERFORMANCE INDUSTRIAL DOORS

A1 (SR1)

B3 (SR2)

C5 (SR3)

**D10 (SR4)**

LPS 1175 CERTIFIED INDUSTRIAL DOORS

## PRODUCT REFERENCE

- Intimidator IR4 Industrial Door

## APPROVED DIMENSIONS

- Maximum width: 8000mm
- Maximum height: 8000mm
- Minimum width: 1750mm
- Minimum height: 1000mm



## SHUTTER CURTAIN

- Double Wall Stainless Steel
- Double Wall Galvanised Steel

## FRAMES/GUIDES

- Two-part galvanised steel guide with rubber seals



## SUBSTRATE

- Reinforced masonry
- Reinforced concrete
- Structural Steelwork
- Sub assembly steel framework

## OPERATION

- Hold-to-run operation with manual locks
- Automatic operation with electronic locks
- Safety on close as assessment directs

## BOTTOM RAIL

- Reinforced steel
- Weather seal

Distributor

