740 SERIES DATA SHEET



BOLT ON ROLLER SHUTTERS FOR LARGER OPENINGS WITH SELF-LOCKING TECHNOLOGY







FEATURES

- Twin skin extruded aluminium lath with compact roll zones
- Self lock technology
- Larger spans possible
- Polyester powder coated to any standard RAL /BS colour



OPTIONS

- · Range of switches and access control
- Can be partially or fully perforated and punched



ALL-ALUMINIUM CONSTRUCTION

- Twin part roll formed aluminium casing
- Slimline extruded aluminium guides
- Smooth and quiet operation with roller guide entry



TYPICAL APPLICATIONS

Suitable new build applications include:

- Medium to high risk commercial buildings
- Public facilities & cultural buildings
- Retail outlets point of sale gantries
- Residential
- Garage doors





740 SERIES DATA SHEET



BOLT ON ROLLER SHUTTERS FOR LARGER OPENINGS WITH SELF-LOCKING TECHNOLOGY

PRODUCT REFERENCE

Xonar 740 Roller Shutter

APPROVED DIMENSIONS

Maximum width: 6000mm Maximum height: 6000mm

Minimum width: 1000mm Minimum height: 1000mm



SHUTTER CURTAIN

60mm twin wall self locking lath

Extruded aluminium profiles

Finish as delivered: polyester powder coated in standard RAL/BS colour

Option to fully or partially perforate or punched

SUBSTRATE

Installation onto:

Brickwork

Blockwork

Steelwork

Timber

OPERATION

Motorised to allow controlled ascent and descent

Tube Motor - Low duty cycle, or where limited to single phase supply

External Drive Motor - High duty cycle or for larger apertures

BOTTOM RAIL

Extruded aluminium section with rubber sealing gasket

Finish as delivered: polyester powder coated in standard RAL/BS colour

FRAMES/GUIDES

Slimline extruded aluminium guides mounted directly to structure

Finish as delivered: polyester powder coated in standard RAL/BS colour

CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or possible to integrate into building management systems and third party alarms

Safety on close as assessment directs

Battery backup options

Distributor

