

943 DATA SHEET



SR2

SR3

SR4

LPS 1175 CERTIFIED BOLT-ON SECURITY SHUTTERS



ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 7, Security Rating 3 (SR3)
- Secured by Design Police Preferred Specification



OPTIONS

- Polyester powder coated to any standard RAL /BS colour
- High or low duty cycle electrical motors
- Can be partially or fully perforated to maintain airflow without compromising security
- Internal and External installations complete with sub assembly steel frames as required



SELF-LOCKING TECHNOLOGY

- No auxiliary locking required - manual or electronic
- Unique profiles lock the shutter in any stop position - fully closed or not
- Allows external first point of entry through the shutter



TYPICAL APPLICATIONS

- High Value Commercial
- Banks and Financial Institutions
- Utilities Buildings
- Data Centres

943 DATA SHEET



SR2

SR3

SR4

LPS 1175 CERTIFIED BOLT-ON SECURITY SHUTTERS

PRODUCT REFERENCE

Xonar 943 Security Shutter

Certified to LPS 1175, Issue 7, Security Rating 3 (SR3)

APPROVED DIMENSIONS

Maximum certified width:
8000mm

Maximum certified height:
10.0m

Minimum certified width:
1000mm

Minimum certified height:
2000mm

SHUTTER CURTAIN

Extruded aluminium self-locking profiles

Finish as delivered: polyester powder coated
in standard RAL/BS colour

Option to fully or partially perforate

OPERATION

Motorised to allow controlled ascent and descent

Tube Motor - Low duty cycle, or where limited to single
phase supply

External Drive Motor - High duty cycle or for larger apertures

CONTROLS

Full range of compatible controls including push button switch,
key switch, radio control or possible to integrate into building
management systems and third party alarms

Safety on close as assessment directs

High duty cycle motor and battery backup options



SUBSTRATE

Certified installation onto:

Brickwork

Blockwork

Concrete

Structural Steelwork

Sub assembly steel framework

BOTTOM RAIL

Reinforced extruded aluminium section with strengthened core

Finish as delivered: polyester powder coated in standard
RAL/BS colour

FRAMES/GUIDES

Heavy duty extruded aluminium guide profiles anchored direct
to the structure

Finish as delivered: polyester powder coated
in standard RAL/BS colour

Distributor