IR2
DATA SHEET

INTIMIDATOR®
HIGH PERFORMANCE INDUSTRIAL DOORS

A1 (SR1) | B3 (SR2) | C5 (SR3) | D10 (SR4) | LPS 1175 CERTIFIED INDUSTRIAL DOORS

ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 8, B3 (SR2)
- Secured by Design Police Preferred Specification

TYPICAL APPLICATIONS

- Medium risk commercial buildings
- Utilities Buildings
- Data centres

OPTIONS

- Aluminium, galvanised steel or stainless steel shutter curtain construction
- Single skin steel curtain construction with full or partial perforation
- Polyester powder coated to any standard RAL/ BS colour
- Manual or auto locking
- High or standard duty cycle motors
- Thermal insulation upgrade
- Acoustic insulation upgrade

LPS 1175: Issue 8
CertNo. 1396f

Assessed to ISO 9001
Cert/LPCB ref.1396

Secured by Design
Police Preferred Specification

CGT security
STRENGTH THROUGH INNOVATION

Intimidator Doors are manufactured in the UK by CGT Security Ltd

IR2
DATA SHEET

INTIMIDATOR®
HIGH PERFORMANCE INDUSTRIAL DOORS

A1 (SR1) | B3 (SR2) | C5 (SR3) | D10 (SR4) | LPS 1175 CERTIFIED INDUSTRIAL DOORS

PRODUCT REFERENCE

- Intimidator IR2 Industrial Door

APPROVED DIMENSIONS

- Maximum width: 8000mm
- Maximum height: 8000mm
- Minimum width 1000mm
- Minimum height: 1000mm

SHUTTER CURTAIN

- Single Wall Aluminium
- Single Wall Galvanised Steel
- Single Wall Perforated Steel
- Double Wall Aluminium
- Double Wall Galvanised Steel
- Double Wall Stainless Steel

SUBSTRATE

- Brickwork
- Blockwork
- Concrete
- Structural Steelwork
- Sub assembly steel framework

FRAMES/GUIDES

- Two-part galvanised steel guide with rubber seals

OPERATION

- Hold-to-run operation with manual locks
- Automatic operation with electronic locks
- Safety on close as assessment directs

BOTTOM RAIL

- Extruded aluminium
- Reinforced steel
- Weather seal

Distributor